## DOCKET: 4925 FAV. Arndt GLAESSERPage 1 of 1

## Milling method

Patent number:

EP1034865 2000-09-13

**Publication date:** Inventor:

FENKEL HARTMUT (DE); PROBST MARTIN (CH); SLEPCEVIC PAUL

Applicant:

ABB ALSTOM POWER CH AG (CH)

Classification:

- international:

B23C3/18; B23C3/00

- european:

B23C3/00; B23C3/18

Application number: EP19990810202 19990308 Priority number(s): EP19990810202 19990308

Also published as:

US6491482 (B1)

JP2000263309 (A)

EP1034865 (B1)


Cited documents:

FR2287962

Report a data error here

## Abstract of EP1034865

The milling tool is guided along a continuous guide path (7) from the outside contour of the raw blank (1) to the contour (2') of the finished part (2) and the raw blank is constantly changed in shape to form the finished part with a constant discharge of material. The continuous path is formed as a two dimensional, flat, spiral-shaped path or as a three dimensional spiral-shaped path. Independent claim describes process for producing continuous guide path by first producing auxiliary lines which run equal to electrostatic field lines (3) between the profile of the finished part and the profile of the raw blank.



Data supplied from the esp@cenet database - Worldwide

USPS EXPRESS MAIL EV 636 851 788 US DEC 12 2005